

# **ERGOLINE PASSION 40/3 SP PLUS**

### **LAMPS**



**BENCH** 

16 @160W 71"

**FACIAL** 

High Pressure UV 3 x 400 W SIDE

N/A

SPAGHETTI

2 x 8W

CANOPY

24 @ 160W 71"

**SHOULDER** 

N/A

**LED TECHNOLOGY** 

N/A

## **POWER**



RATED VOLTAGE

230 V

RATED AMP DRAW 3 Ø

23

RATED FREQUENCY

60 Hz

RATED AMP DRAW 1 Ø

39

**RATED BREAKERS** 

30 amp 3-pole 50 amp 2-pole POWER CONSUMPTION RATING

8,500 W

#### MAINS POWER CONNECTION

- The unit is configured from the factory for connection to 3-Phase power.
- A 3/4" liquid-tight connector is provided

## **PRODUCT SPECIFICATIONS**



NOISE LEVEL 1M AWAY FROM DEVICE

< 66.0 dB

WEIGHT

approx. 805 lbs

NOISE LEVEL INSIDE THE DEVICE

< 70 dB

UNIT FOOTPRINT

94 1/2" X 82 11/16"


LOAD ON THE ACRYLIC PANEL

max. 330 lbs

OPERATING TEMPERATURES


59-89 °F






- \*Owner is responsible for all wiring up to the terminal block connection inside the device. As well as ensuring the wire is properly sized for the amp draw and breaker selection per the electrical code in their area.
- \*\*Minimum footprint size for proper operation and cooling of the unit. Does not account for door sizes or obstructions in the room. (Footprint measurement is not the room size)

## **MEASUREMENTS**







	in.	mm.
В	47 4/16	1,200
B1	30 11/16	780
B2	63/64	25
BL	33 15/32	850
Н	48 7/16	1,230
H1	62 3/16	1,580
L	84 10/16	2,150
L	88 9/16	2,250
L1	84 10/16	2,150
ВК	94 1/2	2,400
TK	82 11/16	2,100

