

SUNRISE 480

TURBO POWER



HIGHLIGHTS

- TURBO POWER
- TOP COOLING
- INTERIOR LIGHT
- STEREO SOUND
- VOICE GUIDE



Ergoline

SUNRISE 480 | TURBO POWER



The Sunrise is not only known for being a respected investment, but also for creating beautiful results for your customers. Whether you are reinforcing your current line-up or bringing in something new for your customers to try, the Sunrise will give your comfort features, high-performance color and easy operation.

ERGOLINE, A BRAND OF JK PRODUCTS & SERVICES, INC.

411 West Washington Avenue, Suite B | Jonesboro, AR 72401

☎ Toll-free: 888.771.0996 | www.ergoline.us

CONTRAINDICATIONS:

Follow Instructions. Avoid over-exposure as with natural sunlight. Over-exposure can cause eye or skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. ALWAYS WEAR PROTECTIVE EYEWEAR! Failure to do so may result in severe burns or long term injury to the eyes. Certain medications or cosmetics may increase your sensitivity to ultraviolet radiation. Consult a physician before using sunlamps if you are using medication, have a history of skin problems or believe yourself to be especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product. Please refer to the recommended exposure schedule for your skin type and do not tan more than once in a 24-hour period. Attention: This sunlamp product should not be used on persons under the age of 18 years. Persons who should not use this device include anyone who is sunburned, has open wounds, is naturally pale, has discolored patches of skin, has an increased risk of skin cancer, is being treated for or taking medicine causing photosensitivity, is pregnant, has atypical moles or more than 16 moles on their body (2mm diameter or larger). © 2020 JK Products & Services, Inc.

PERFORMANCE	Session Time	9 minutes
	Technology	Turbo Performance
	Low pressure lamps	48 x 200 W
	Facial tanner	-
	Spaghetti lamps	-
COMFORT	Shoulder Tan	-
	Air conditioning	Top Cooling
	Ventilation	-
	Aqua Fresh / Aroma	-
	Sound	3D Sound System
HANDLING	Smart phone connection	MP3 AUX
	Acrylic	-
	External display	-
	Internal display	✓
	NFC Connect	-
DESIGN	Voice Guide	✓
	Set-up Manager	-
	Miscellaneous	-
	External lighting	-
	Internal lighting	-
TECHNICAL SPECIFICATIONS	Dimensions closed	54-13/16 x 75-5/16 x 92-3/16
	Dimensions open (L x W x H in)	54-13/16 x 75-5/16 x 92-3/16
	Minimum Recommended Room Size (L x W ft)	8 x 7
	Unit Footprint (L x W in)	76-3/16 x 94-1/2 x 102-3/8
	Max. power consumption with 400/415 V 3N power supply with 230 V 1N power supply	11,300 W
ELECTRICAL SPECIFICATIONS	Fuse (delayed action)	40 amp 3 Ø 70 amp single Ø
	Weight	1,202 lb
	Rated frequency	60 Hz
	Rated voltage	230 V
	Rated amp draw 3 Ø	31
	Rated amp draw 1 Ø	52
	Mains Power Connection	The unit is configured from the factory for connection to 3-Phase power. A 1" liquid-tight connector is provided. *Owner is responsible for all wiring up to the terminal block connection inside the device. As well as ensuring the wire is properly sized for the amp draw and breaker selection per the electrical code in their area.
	Load on the acrylic panel	max. 330 lbs.
	Operating Temperature	59-89 (degrees) F
	Number of body lamps	48 @ 200W 2M